



FEATURED HIGHLIGHTS

- Bi-material shaft with Stainless Steel AISI 304 drive-end
- SKF sealed bearings
- Thermal protection (single phase), IE2 compliant (tri-phase <0.75kW), IE3 compliant (tri-phase >0.75kW)
- IP-X5
- Inlet/Outlet - 1.5" BSP tapped
- Ø Unions - 50 mm
- Unions included - No
- Salt resistancy - 0.40%

FEATURES

XL pre filter basket

1/4 turn opening lid

Quick self priming

One-piece pump body

BENEFITS

Longer periods between cleanings

Easy opening and locking

Quick and safe start of the pump

Super silent

DIMENSIONS AND PERFORMANCE

Model	Flow m ³ /hr @ 8m	Power Output (kW/HP)	Full Load (A)	Volt (V)	Phase	Length (A)(mm)	Weight (Kg)
P-SFL-05IE2	12	0.37/0.5	2.7	220-240	1~	545	13.8
P-SFL-07IE2	15	0.55/0.75	4.4	220-240	1~	545	14.1
P-SFL-10IE2	18	1.1/1	5	220-240	1~	545	14.6
P-SFL-15IE2	21	1.4/1.5	6.2	220-240	1~	575	15.6
P-SFL-20IE2	23	1.5/2	6.7	220-240	1~	575	17
P-SFL-30IE2	29	2.1/3	9.6	220-240	1~	575	23.3
P-SFL-073	15	0.55/0.75	3.1-1.8	380-420	3~	545	12.5
P-SFL-103E3	18	0.75 / 1	3.3-1.9	230 / 400	3~	545	13.9
P-SFL-153E3	21	1.1/1.5	4.3-2.4	380-420	3~	575	22.3
P-SFL-203E3	23	1.5/2	6.0-2.7	380-420	3~	575	23.9
P-SFL-303E3	29	1.75/3	6.45-3.3	380-420	3~	575	30

