

WHISPERFLO

SINGLE SPEED SWIMMING POOL PUMPS



FEATURED HIGHLIGHTS

- Induction asynchronous motor
- Bi-material shaft with Stainless Steel AISI 304 drive-end
- SKF sealed bearings
- Thermal protection (single phase), IE2 compliant (tri-phase <0.75kW), IE3 compliant (tri-phase >0.75kW)
- IP-X5
- Inlet/Outlet - 2" BSP tapped
- Ø Unions - 50 mm or 63 mm
- Unions included - No
- Salt resistancy - 0.40%

FEATURES

- 1/4 turn opening lid
- Quick self priming
- One-piece pump body

BENEFITS

- Easy opening and locking
- Quick and safe start of the pump
- Super silent

DIMENSIONS AND PERFORMANCE

Model	Flow m ³ /hr @ 8m	Power Output (kW/HP)	Full Load (A)	Volt (V)	Phase	Length (A)(mm)	Weight (Kg)
P-WFL-071E2	15	0.55 / 0.75	4.4	230	1~	545	14.1
P-WFL-101E2	19	0.75 / 1	5.1	230	1~	545	14.6
P-WFL-151E2	23	1.1 / 1.5	5.6	230	1~	575	15.6
P-WFL-201E2	24	1.5 / 2	6.6	230	1~	575	17
P-WFL-301E2	32	2.2 / 3	8.5	230	1~	575	23.3
P-WFL-073	15	0.55/0.75	3.1-1.7	230/400	3~	545	12.5
P-WFL-103E3	19	0.75 / 1	3.3-1.9	230 / 400	3~	545	13.9
P-WFL-153E3	23	1.1/1.5	4.3-2.5	230/400	3~	575	22.3
P-WFL-203E3	24	1.5 / 2	6.5-2.9	230 / 400	3~	575	23.9
P-WFL-303E3	32	2.2 / 3	6.5-3.3	230 / 400	3~	575	30

